

## State Button Detection

<http://arduino.cc/en/Tutorial/ButtonStateChange>

### HARDWARE REQUIRED

Arduino Board  
1 momentary button or switch  
1 10K ohm resistor  
1 LED  
1 220ohm Resistor  
breadboard  
hook-up wires


### CIRCUIT

Once you've got a pushbutton working, you often want to do some action based on how many times the button is pushed. To do this, you need to know when the button changes state from off to on, and count how many times this change of state happens. This is called state change detection or edge detection.


When the pushbutton is open (unpressed) there is no connection between the two legs of the pushbutton, so the pin is connected to ground (through the pull-down resistor) and we read a LOW. When the button is closed (pressed), it makes a connection between its two legs, connecting the pin to voltage, so that we read a HIGH. (The pin is still connected to ground, but the resistor resists the flow of current, so the path of least resistance is to +5V.)

If you disconnect the digital i/o pin from everything, the LED may blink erratically. This is because the input is «floating» - that is, not connected to either voltage or ground. It will more or less randomly return either HIGH or LOW. That's why you need a pull-down resistor in the circuit.

### IMAGE



## SCHEMATIC



## CODE

```

// this constant won't change:
const int buttonPin = 2; // the pin that the pushbutton is attached to
const int ledPin = 13; // the pin that the LED is attached to

// Variables will change:
int buttonPushCounter = 0; // counter for the number of button presses
int buttonState = 0; // current state of the button
int lastButtonState = 0; // previous state of the button

void setup() {
  // initialize the button pin as a input:
  pinMode(buttonPin, INPUT);
  // initialize the LED as an output:
  pinMode(ledPin, OUTPUT);
  // initialize serial communication:
  Serial.begin(9600);
}

void loop() {
  // read the pushbutton input pin:
  buttonState = digitalRead(buttonPin);

  // compare the buttonState to its previous state
  if (buttonState != lastButtonState) {
    // if the state has changed, increment the counter
    if (buttonState == HIGH) {
      // if the current state is HIGH then the button went from off to on:
      buttonPushCounter++;
      Serial.println("on");
      Serial.print("number of button pushes: ");
      Serial.println(buttonPushCounter);
    } else {
      // if the current state is LOW then the button went from on to off:
      Serial.println("off");
    }
  }

  // turns on the LED every four button pushes by
  // checking the modulo of the button push counter.
  // the modulo function gives you the remainder of the division of two numbers:
  if (buttonPushCounter % 4 == 0) {
    digitalWrite(ledPin, HIGH);
  } else {
    digitalWrite(ledPin, LOW);
  }

  // save the current state as the last state, for next time through the loop
  lastButtonState = buttonState;
}

```

/\*

State change detection (edge detection)

Often, you don't need to know the state of a digital input all the time, but you just need to know when the input changes from one state to another. For example, you want to know when a button goes from OFF to ON. This is called state change detection, or edge detection.

This example shows how to detect when a button or button changes from off to on and on to off.

The circuit:

- \* pushbutton attached to pin 2 from +5V
- \* 10K resistor attached to pin 2 from ground
- \* LED attached from pin 13 to ground (or use the built-in LED on most Arduino boards)

created 27 Sep 2005

modified 30 Aug 2011

by Tom Igoe

This example code is in the public domain.

<http://arduino.cc/en/Tutorial/ButtonStateChange>

\*/